

Surface Mount Fuse, 1.6 x 0.8 mm, Super-Quick-Acting FF, 63 VDC

new



35 mA



50 mA

UL 248-14 · 63VDC · Super-Quick-Acting FF

See below:

[Approvals and Compliances](#)

Description

- Impermeable to potting compound used to achieve hermetic seal for use in intrinsically safe applications according to ATEX and IECEx requirements.
- Low melting I²t-values, fast interruption
- Low current solid state fuse (35mA, 50mA)

Applications

- Intrinsically safe electronics
- Control electronics
- DC Secondary Protection

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Microsite](#)

Technical Data

Rated Voltage	63VDC
Rated current	0.035 - 0.05 A
Breaking Capacity	50 A
Characteristic	Super-Quick-Acting FF
Mounting	PCB,SMT
Admissible Ambient Temp.	-50 °C to +125 °C
Climatic Category	50/150/21 acc. to IEC 60068-1
Material: Housing	Glass
Material: Terminals	Copper, Ni/Au-plated
Unit Weight	0.0017 g
Storage Conditions	0 °C to 40 °C, max. 70% r.h.
Product Marking	see variants

Soldering Methods	Reflow Soldering Profile
Solderability	245 °C / 3 sec acc. to IEC 60068-2-58, Test Td
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-58
Moisture Sensitivity Level	MSL 1, J-STD-020
Thermal Shock	MIL-STD-202, Method 107
ESD classification	IEC 61000-4-2 Level X (Test Voltage ≤ 125V)
Resistance to Solvents	MIL-STD-202, Method 215

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: USL 0603

Approval Logo	Certificates	Certification Body	Description
	UL Approvals	UL	UR File Number: E41599


Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	UL 248-14	Low voltage fuses - Part 14: Supplemental fuses
	Designed according to	CSA22.2 No. 248.14	Low-Voltage Fuses - Part 14: Supplemental Fuses







Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

Compliances



The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	Halogen Free	SCHURTER AG	SCHURTER strives to offer our customers halogen free products.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.


Dimension [mm]

H 1.6 mm

Reflow soldering pads




Derating Curves



Pre-Arcing Time

Rated Current In	1.0 x In min.	2.5 x In max.	10.0 x In max.
35 mA - 50 mA	4 h	5 s	1 ms

Time-Current-Curves



Variants

Rated Current [A]	Rated Voltage [VDC]	Marking	Breaking Capacity	Voltage Drop 1.0 I _n max. [mV]	Cold Resistance typ. [Ω]	Melting I ² t 10.0 I _n typ. [μ(A ² s)]	Order Number
0.035	63	blue	1)	310	7.3	-	0.18 ● 3-124-964
0.05	63	red	1)	145	2.7	-	0.34 ● 3-124-969

1) UL: 50 A @ 63 VDC, tau <0.2 ms; Additional internal testing: 100 A @ 125 VDC, tau <0.2 ms

Availability for all products can be searched real-time: <https://www.schurter.com/en/info-center/support-tools/stock-check-distributors>

Packaging Unit

acc. IEC 60286-3 Type 2a

5000 pcs. in tape [W: 8mm and P1: 4mm] on reel [A: 18cm]